Rapidly Constructed Large-Bar Precast Bridge Bent Seismic Connection

Description

Meta Fields

Project Completion Year: 2008 Project Starting Year: 2008

Other Documents 0 Other Documents File: 2337

Primary Sponsor Contact Info: Washington State Department of Transportation Research Office

Transportation Building, MS 47370 Olympia, WA 98504 USA Kim Willoughby 360-705-7978

Budget: 0.00 Key Words:

Precast concrete, bridge substructures, bents, bridge column, accelerated bridge construction, anchorage, ducts

Abstract:

The use of precast components in bridge bents can accelerate bridge construction, but their use in seismic systems is challenging. Such systems must have connections that are both easy to assemble on site, and have sufficient strength and ductility during earthquakes. A precast bridge bent beam-column connection that is suitable for rapid construction in seismic regions has been developed and tested. The connection features a small number of large (#18) vertical column bars grouted into large corrugated ducts embedded in the cap-beam. This combination provides speed and simplicity of erection, as well as generous construction tolerances. Lateral-load tests on the system showed that it has strength and ductility similar to those of a comparable cast-in-place connection, and that deliberate debonding of a short length of the bars has little effect on its seismic performance.

Subject: Grouted Ducts

Group: Seismic

Category: Completed Projects