

# Rapid Replacement of the Hood Canal Bridge Approach Spans



**Joseph Merth, P.E.**  
Bridge Design Engineer

3 June 2008



# Overview

- Introduction
- Current Project
- Approach Design
- Approach Construction
- Challenges



*East Approach*



*Floating Structure*



*West Approach*

# Location

Hood Canal  
Bridge

Puget Sound


Seattle

Olympic  
Peninsula








# Location











Hood Canal Bridge


LOCATION OF FERRY PARKING (SHINE PIT)

PORT GAMBLE FERRY TERMINAL

SOUTH POINT FERRY TERMINAL

HOOD CANAL





Transition Span

West Half Floating Structure

West Approach

Draw Span

Transition Span

East Half Floating Structure

East Approach


# Bridge Facts



- Length – 7869 feet  
(Longest floating bridge over salt water)
- Floating portion – 6530 feet
- Max water depth – 340 feet
- Tidal Variation – 16.5 feet
- Center draw span opening – 600 feet

# Bridge History

- Original Construction – January 1958
- Open to traffic – 12 August 1961





# West Half Fails

- February 13, 1979
- Sustained winds of 85mph
- 120mph gusts




# West Half Replacement

- Reopened Oct. 25<sup>th</sup>, 1982
- Post-tensioned pontoons
- Increased anchor size






# Current Project





# Approaches

- Provide fixed link from shore to floating structure
- Help resist longitudinal wind and wave forces from the floating structure




# Original West Approach

- 2 – span haunched steel PL Girder
- 190' length
- Buttress added for West half replacement





3 June 2008





# Original East Approach

- 6 – span haunched steel PL Girder
- 643' length
- Wind/Wave forces – Pier 4





# Approach Retrofit

- Original Retrofit Requirement
  - Deck Replacement
  - Seismic Retrofit
  - Pier 4 retrofit (add buttress wall)
- Required 6-8 week closure



West




East

# Approach Replacement

- Replace entire approaches (superstructure/substructure)
- Build to current standards – 40' roadway, seismic
- Ability to widen to 4 lanes (60') in the future




# Typical Section



# West Approach Elevation


- 1 span (W83G Girders)
- 154' total length





# East Approach Elevation

- 5 spans (W74G Girders)
- 609' total length



# Replacement Challenges

- Limited closure – extended weekend
  - Construct superstructure adjacent to existing approach
- Distribute wind/wave forces into East Approach






# Rolling Scheme



3 June 2008

# Rolling Scheme


## Prior to Rollover






# Rolling Scheme

## Prior to Rollover




# Rolling Scheme

## Prior to Rollover




# Rolling Scheme

## Prior to Rollover






# Rolling Scheme During Rollover




# Rolling Scheme

## During Rollover




# Rolling Scheme During Rollover






# Rolling Scheme During Rollover




# Rolling Scheme During Rollover




# Rolling Scheme

## After Rollover



# Rolling Scheme


## After Rollover






# Rolling Scheme


## After Rollover




# Wind/Wave Forces



# Hinge Diaphragm




# Hinge Diaphragm







# Hinge Diaphragm




# Hinge Diaphragm



# Hinge Diaphragm





# Hinge Diaphragm





# Rolling Assembly




*Hilman Roller*

Temp.  
Elast.  
Brg.


Hilman  
Roller

Rolling  
Plate



**Section A-A**

# Hilman Rollers



## West Approach

- 1 span
- 1000 kip DL/Pier
- 2000 kips Total
- 2 Hilman rollers/span (300 ton capacity)

## East Approach


- 5 spans
- 800 to 1500 kips DL/Pier
- 7600 kips Total
- 2 Hilman rollers/span (300 or 500 ton capacity)

# Construction



# Work Trestle

- Trestle and Falsework scheme included in Contract
- Contractor required to submit for review and approval
- Falsework system designed for  $\frac{1}{2}$  seismic acceleration (0.15g)





# Work Trestle

- 58,000 ft<sup>2</sup>
- 260 – 2' Diameter Piles
- 4 months to construct

} East Approach





# Substructure

- 12 – 10' Diameter Shafts
  - 5 ½ Months Construction
  - Epoxy Coated Rebar – Entire Structure
- } East Approach




# Superstructure



# Hydraulic Jacking – Horizontal

- West Approach – 2 synchronized jacks
- East Approach – 6 synchronized jacks
- Max horizontal force/jack – 30 to 80 kips
- Max ¼” differential horizontal movement between adjacent piers during rolling






# Hydraulic Jacking – Horizontal

Rolling  
Plate



Jacking  
Rod






# The Rollover




3 June 2008


# Hydraulic Jacking – Vertical




# Hydraulic Jacking – Vertical



# Hydraulic Jacking – Vertical




# Hydraulic Jacking – Vertical






# Hydraulic Jacking – Vertical



Rolling  
Plate

# Hydraulic Jacking – Vertical

- Jacking performed pier by pier
- 10 synchronized jacks interior piers, 5 at end piers
- Max relative differential movement between jacks =  $\frac{1}{4}$ "
- Max relative differential movement between piers = 2"
- Pressure system used for vertical jacking



# East Approach Aerial Photos




Before

During


After

# Approach Closure Schedule

## West Approach



## East Approach





# Closure Challenges






# Abutment and Approach Slabs


- Precast Abutment Endwall
- Precast Approach Slabs




# Abutments




# Abutments



# Abutments




# Abutments







# Abutments



# Abutments



# Abutments



# Precast Abutment Endwall Construction

Precast Endwall

Cast-in-place Endwall



*Cast-in-Place Endwall*

*Precast Endwall*



# Precast Abutment Endwall Construction

Precast Backwall

Voids



Backfill






# Precast Approach Slab

- 6 Sections
- 25' x 8' x 1'-1"






# Expansion Joints



3 June 2008


# Lessons Learned

## Unequal Bearing Loads




# Lessons Learned

## Unequal Bearing Loads



# Lessons Learned


## Unequal Bearing Loads






# Lessons Learned

## Unequal Bearing Loads




# Lessons Learned

## Unequal Bearing Loads



# Lessons Learned

## Unequal Bearing Loads



# Lessons Learned

- Unequal Bearing Loads
- Jacking and shimming required

Design DL = 300 kips  
Estimated DL = 500 kips



*After Shimming*



*Prior to Shimming*



3 June 2008